



Overview

Model Name	APC Power-Saving Back-UPS Pro 550
Includes	CD with software , USB cable , User Manual , Warranty card
Standard Lead Time	Usually in Stock
Product Distribution	Albania , Algeria , Andorra , Angola , Antigua And Barbuda , Armenia , Australia , Austria , Azerbaijan , Bahrain , Belarus , Belgium , Benin , Bolivia , Bosnia And Herzegovina , Botswana , Bulgaria , Burkina Faso , Burundi , Cameroon , Cayman Islands , Central African Republic , Chad , Chile , Congo , CONGO, THE DEMOCRATIC REPUBLIC OF THE , <![CDATA[Cote D'Ivoire]]> , Croatia , Cyprus , Czech Republic , Denmark , Djibouti , Dominica , Egypt , Equatorial Guinea , Eritrea , Estonia , Ethiopia , Fiji , Finland , France , Gabon , Gambia , Georgia , Germany , Ghana , Gibraltar , Greece , Grenada , Guadeloupe , Guinea , Guyana , French Guiana , Hungary , Iceland , Indonesia , Iran (Islamic Republic Of) , Iraq , Ireland , Israel , Italy , Jordan , Kazakhstan , Kenya , KOREA, REPUBLIC OF , Kuwait , Latvia , Lebanon , Lesotho , Liberia , Liechtenstein , Lithuania , Luxembourg , Macedonia , Malawi , Malaysia , Mali , Malta , Martinique , Mauritania , Moldova, Republic Of , Mongolia , Morocco , Mozambique , Namibia , Netherlands , New Zealand , Niger , Nigeria , Norway , Oman , Pakistan , Paraguay , Peru , Philippines , Poland , Portugal , Romania , Russian Federation , Rwanda , SAINT KITTS AND NEVIS , SAINT VINCENT AND THE GRENADINES , Saudi Arabia , Senegal , Sierra Leone , Singapore , Slovakia (Slovak Republic) , Slovenia , Somalia , South Africa , Spain , Sri Lanka , Sudan , Suriname , Sweden , Switzerland , Tajikistan , TANZANIA, UNITED REPUBLIC OF , Thailand , Togo , Tunisia , Turkey , Turkmenistan , Uganda , Ukraine , United Arab Emirates , Uruguay , Uzbekistan , Viet Nam , Western Sahara , Yemen , Zambia , Zimbabwe

Output

Output Power Capacity	330 Watts / 550 VA
Max Configurable Power (Watts)	330 Watts / 550 VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	50 Hz
Output Frequency (sync to mains)	Line Interactive
Waveform Type	Stepped approximation to a sine wave
Output Connections	(2) IEC Jumpers (Battery Backup) , (3) IEC 320 C13 (Battery Backup) , (3) IEC 320 C13 (Surge Protection)

Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC-320 C14

Input voltage range for main operations	176 - 282 V
Input voltage adjustable range for mains operation	155 - 290V
Maximum Input Current	6 A
Input Breaker Capacity	7 A

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	12 hour(s)
Replacement Battery	APCRBC110
RBC Quantity	1

Communications & Management

Interface Port(s)	Optional Simple Signalling RS232 cable , USB
Available SmartSlot™ Interface Quantity	0
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	420 joules
Filtering	Full time multi-pole noise filtering :10% of IEEE surge let-thgouh : zero clamping response time: instantaneous
Data Line Protection	Network line - 10/100/1000 Base-T Ethernet (RJ-45 connector)

Physical

Maximum Height	190.0 mm
Maximum Width	91.0 mm
Maximum Depth	310.0 mm
Rack Height	0 U
Net Weight	6.53 kg
Shipping Weight	7.71 kg
Shipping Height	252.0 mm
Shipping Width	138.0 mm
Shipping Depth	442.0 mm
Master Carton Units	2.0
Master Carton Weight	15.94 kg
Color	Black
SCC Codes	1073130426688 1
Units per Pallet	48.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	45.000 dB

Conformance

Approvals	A-tick , C-tick , CE , GOST , GS Mark
Standard warranty	2 years repair or replace , 3 years repair or replace for European Union countries
Equipment protection policy	Lifetime : 150000 Euros , Lifetime : 200000 AUD , Lifetime : 75000 GBP

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs